

**BALL VALVE KPC  
FULL BORE, DN25–DN200**

	<p>DN25–DN50 <span style="float: right;">CE</span></p>
	<p>DN65–DN150 <span style="float: right;">CE</span></p>
	<p>DN200 <span style="float: right;">CE</span></p>



**Working temperature -10 °C/+150 °C**

1	Body	Ductile Iron – GGG40
2	Ball	Brass – MS 58 – Chrome plated
3	Stem	Brass – MS 58
4	Seats	PTFE
5	O-Ring	EPDM
6	Handle	Iron – St 37-3

**KPC DN ... PN16 DP EB PB****PN16**

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A953013	25	125	115	76	25	150	18	85	14	4	F03	14x10	3,50
A953015	32	130	140	92	31	235	18	100	18	4	F04	17,6x12	5,30
A952017	40	140	150	97	39	235	18	110	18	4	F05	17,6x12	6,60
A952018	50	150	165	105	49	271	20	125	18	4	F05	17,6x12	8,80
A952019	65	170	185	124	63	288	18	145	18	4	F07	23,6x17	11,40
A952020	80	180	200	133	76	288	20	160	18	8	F07	23,6x17	14,00
A952021	100	190	220	153	100	288	20	180	18	8	F07	23,6x17	17,00
A952022	125	200	250	183	125	541	22	210	18	8	F10	31,6x19	30,00
A952050	125	325*	250	183	125	541	22	210	18	8	F10	31,6x19	30,00
A952023	150	210	285	203	150	541	22	240	22	8	F10	31,6x19	37,00
A952053	150	350*	285	203	150	541	22	240	22	8	F10	31,6x19	37,00
A952024	200	400*	340	316	200	1000	24	295	22	12	F12	K30	84,00

**KPC DN ... PN40 DP EB PB****PN40**

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A953013	25	125	115	76	25	150	18	85	14	4	F03	14x10	3,50
A953015	32	130	140	92	31	235	18	100	18	4	F04	17,6x12	5,30
A952017	40	140	150	97	39	235	18	110	18	4	F05	17,6x12	6,60
A952018	50	150	165	105	49	271	20	125	18	4	F05	17,6x12	8,80